

ProColor Stain Guard Grout Additive

**A patented admixture that eliminates
the need to seal tile grout**

**Now with a
20 Year Product
Warranty!**

- Effortless protection for grouts
 - Stain, mold and mildew resistance
 - Unaffected by normal household cleaners
- Time and money savings
 - No return trips or extra labor to seal grout
- Easy to use
 - Mix in place of water
 - Low odor
 - Easy clean up
- Versatile
 - Can be used indoor and outdoor
 - Can be used with sanded or unsanded grout



Save time, money and hassle with ProColor Stain Guard Additive – Grout, clean and your done. No need to seal!

Traditional Sealer vs. ProColor Stain Guard Additive

Example: 175 sq. ft. bathroom	
Grout dry time before sealer can be applied	3-7 days*
Drive time to job site	30 minutes
Clean grout / time to dry	70 minutes
Apply sealer	20 minutes
Sealer soak time / clean up time	40 minutes
Drive time to next jobsite	30 minutes
Total additional time at site	3 hours & 10 minutes
Total additional time for project completion	3.5 - 7.5 days

*Sealer manufacturer recommends grout to dry completely (3-7 days) before application.

See our full line of trusted ProSpec solutions

ProSpec Polymer-Modified Tile Setting Mortars

Offering a full line of portland cement-based and rapid setting tile mortars.

- Polymer-modified mortars that can bridge cracks, bond to difficult substrates, adhere large format tiles and more
- Engineered performance mortars offering superior bond strength



ProSpec ProColor Grout

Polymer-modified, portland cement-based sanded and unsanded grouts.

- Rich consistent color
- Excellent workability with easy cleanup



ProSpec ProColor Advantage Caulk

- Superior flexibility with up to 500% elongation
- Color and texture match with ProSpec ProColor grouts
- Cures in wet environments



ProSpec® is a registered trademark
of Bonsal American, Inc., an Oldcastle company
Bonsal American • 8201 Arrowridge Blvd. • Charlotte, NC 28273
Phone: 1.800.334.0784 • prospec.com

PROSPEC®