


REV.	DESCRIPTION	DATE	APP'D	REV.	DESCRIPTION	DATE	APP'D		
REVISIONS				REVISIONS					

This document contains proprietary data for products designed by Shallco, Inc., of Smithfield, NC. No disclosure; reproduction, or use of any part thereof maybe made except by written permission.

	NAME	DATE
DRAWN	JRT	9-25-19
CHECKED		
ENG APPR.	RMF	9-25-19
MFG APPR.		
Q.A.		

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL $\pm 1/32$
ANGULAR: MACH \pm BEND \pm
TWO PLACE DECIMAL $\pm .010$
THREE PLACE DECIMAL $\pm .005$

			
308 COMPONENTS DRIVE, SMITHFIELD, NC 27577 USA			
DO NOT SCALE DRAWING			
TITLE: BI-STABLE RELAY 24/28VDC-200AMP W/HARDWARE & DIODES			
BLANK WEIGHT: -		PART WEIGHT: 1.1	
SIZE A	DWG. NO. BR-200-24-1-34	REV. B	
SHEET 1 OF 2			
SCALE: 1:2	FILENAME: BR-200-24-1-34 WEBSITE	WWW.SHALCO.COM	

Bi-Stable Relay Technical Data

Temperature range: -40 C to +85°C
 -40°F to +185°F
 Max. Altitude rating: 50,000 ft.
 Seal: IP67: IEC 60529
 Shock: 6g, 11ms, Saw Tooth
 Vibration: SAE J1455, Appendix A Cat. 2,
 4g - 10Hz-2000Hz

Electrical Characteristics

Min. Insulation Resistance: 100 MΩ
 Dielectric withstanding voltage: 1050 V / 1 min.
 Max. Contact drop, initial: 150 mV
 (CTQ <0.0009 VDC @ 1AMP, MAX)
 Duty rating, Continuous: 200 A

Rated Contact Load 24/28 VDC

Resistive load: 50,000 cycles 200 A
 Inductive load: 10,000 cycles 100 A
 Motor load: 50,000 cycles 200 A
 Bounce: ≤ 5 ms
 Break: ≤ 5 ms

Coil Data 24/28 VDC

Nominal voltage: 24/28 VDC
 Voltage range: 18-32 VDC
 (CTQ @ 14VDC)
 Pull closed coil resistance: 7.3 Ω, ± 10%
 Pull open coil resistance: 8.4 Ω, ± 10%
 Minimum Pulse Length: 100ms
 Maximum Pulse Length: 400ms
 Max. operations per minute: 6 (Momentary Pulse)

PROPRIETARY AND CONFIDENTIAL

This document contains proprietary
 data for products designed by
 Shallco, Inc., of Smithfield, NC.
 No disclosure, reproduction, or use
 of any part thereof may be made
 except by written permission.

	NAME	DATE
DRAWN	JRT	9-25-19
CHECKED		
ENG APPR.	RMF	9-25-19
MFG APPR.		
Q.A.		



SHALLCO

308 COMPONENTS DRIVE, SMITHFIELD, NC 27577 USA

DO NOT SCALE DRAWING

TITLE:

BI-STABLE RELAY
24/28VDC-200AMP
W/HARDWARE & DIODES