

HMG Fuse Holder

The HMG fuse holder accepts industry standard AMG (Mega) fuses for primary fusing applications. The narrow rugged body makes it ideal for demanding environments such as 'under the hood' locations in construction, agriculture, heavy trucking and specialty vehicle applications.

Specifications

Rating: For use with AMG (Mega) fuses from 100A - 300A

Temperature rating: -40°F (-40°C) to 260°F (125°C)

Materials: UL 94 V-0 thermoplastic with zinc-plated steel studs

Termination: M8 or 5/16-18 threaded studs and hex nuts for fuse mounting. Wire sizes: #8 AWG - 1/0

Torque rating: 150 in-lbs max

Mounting torque rating: Optional mounting hole patterns, 44 in-lbs max

Features

Side-stackable

Bottom side can be insulated from the mounting panel

Splash resistant cover



Ordering information

HMG - X X X

Series	Base	Hardware Options	Cover
HMG = HMG fuse holder	1 = Tie wrap mount 2 = Offset mounted	1 = 5/16-18 studs w/nuts installed 2 = 5/16-18 studs w/nuts bulk 3 = 5/16-18 studs w/o nuts 4 = M8 x 1.25 studs w/nuts installed 5 = M8 x 1.25 studs w/nuts bulk 6 = M8 x 1.25 studs w/o nuts	0 = None 1 = Cover installed 2 = Cover bulk

Dimensions in mm (inches)

