



S 10 N - 10 G - ST Dispersing element

Suitable for dispersing instrument T 10 basic and T 10 standard
 ST tools are recommended for use with tissue and other fibrous materials*
 Working range: 1 - 100 ml
 Stator diameter: 10 mm
 Immersion depth: 22 - 100 mm
 Materials in contact with medium: PTFE, AISI 316L
 Suitable for solvents
 Max. temperature: 180 °C
 Sterilization methods: all methods

Technical Data

Volume range min. (H2O) [l]	0.001
Volume range max. (H2O) [l]	0.1
Stator diameter [mm]	10
Rotor diameter [mm]	7.5
Gap between rotor and stator [mm]	0.25
allowable Speed max. [rpm]	30000
Circumferential speed max. [m/s]	11.8
Immersion depth min. [mm]	23
Immersion depth max. [mm]	100
Shaft length [mm]	115
Material in contact with medium	PTFE, AISI 316L
pH min.	2
pH max.	13
Suitable for solvents	yes
Suitable for abrasive substances	yes
Working temperature max. [°C]	180
Sterilization methods	all methods
Ultimate fineness, suspensions min. [µm]	5
Ultimate fineness, suspensions max. [µm]	25
Ultimate fineness, emulsions min. [µm]	1
Ultimate fineness, emulsions max. [µm]	10

Ident. No.

0004446700