



Introducing the all new
Cavitator® line of Ultrasonic Cleaners

- Five Cavitator Cleaner models ranging from 3.1 quarts to 18 gallons
- Heater included on all models
- Digital timer and heater displays and controls
- Stainless steel baskets and covers included
- Smudge-free stainless surface on most cleaners
- Drain valves included on all cleaners except 3L
- Handles on smaller cleaners for easy lifting
- Two fixed wheels and two omnidirectional wheels with locks on the 18G



Mettler Electronics Corp.
www.mettlerelectronics.com
Toll Free: 1.800.854.9305



Extra baskets are available for the 3L, 6L, 10L and 22L Cavitator ultrasonic cleaners. Load one basket up while another is processing!

Use baskets to hold items for cleaning and safely remove them from the cleaner when they are finished.

Extra lids are available for the 3L, 6L, 10L and 22L Cavitator ultrasonic cleaners.

Use lids to trap biologically-active contaminants and reduce noise while the cleaner is in operation.



New Cavitator® Ultrasonic Cleaner Specifications

Mettler P/N	Picture	Description	Included accessories	Power	Timer	Temperature (G)	Tank size-mm (inches)	Dimensions of cleaner-mm (inches)	Weight Kg of the outer cover (lbs)	Material of the cover	Watts	Watts / heater
ME 3L		Digital, CE,EMC,ROHS,FCC	Stainless steel basket and cover	110VAC / 60 Hz or 220VAC / 50 Hz	0 - 30 minutes	20 - 80°C	3 L (0.8)	240 x 135 x 100 (9.4 x 5.3 x 3.9) SUS304	270 x 170 x 210 (10.6 x 6.7 x 8.3) (4.8)	Stainless steel	120 W	100 W
ME 6L		Digital, drainage ball valve, heat dissipation fan, CE,EMC,ROHS,FCC	Stainless steel basket and cover	110VAC / 60 Hz or 220VAC / 50 Hz	0 - 30 minutes	20 - 80°C	6 L (1.6)	300 x 150 x 150 (11.8 x 5.9 x 5.9) SUS304	330 x 180 x 270 (13 x 6.7 x 10.6) (6.13.2)	Stainless steel	180 W	200 W
ME 10L		Digital, drainage ball valve, heat dissipation fan, CE,EMC,ROHS,FCC	Stainless steel basket and cover	110VAC / 60 Hz or 220VAC / 50 Hz	0 - 30 minutes	20 - 80°C	10 L (2.6)	300 x 240 x 150 (11.8 x 9.4 x 5.9) SUS304	330 x 270 x 270 (13 x 10.6 x 10.6) (8.17.6)	Stainless steel	240 W	250 W
ME 22L		Digital, drainage ball valve, heat dissipation fan, CE,EMC,ROHS,FCC	Stainless steel basket and cover	110VAC / 60 Hz or 220VAC / 50 Hz	0 - 30 minutes	20 - 80°C	22 L (5.8)	500 x 300 x 150 (19.7 x 11.8 x 5.9) SUS304	550 x 330 x 270 (21.6 x 13 x 10.6) (1.3 (28.6))	Stainless steel	480 W	600 W
ME 18G*		Fill hose, drainage valve, 2 fixed wheels and 2 omni-directional wheels with locks, heat dissipation fan, CE	Stainless steel basket and cover	110VAC / 60 Hz or 220VAC / 50 Hz	0 - 99 minutes	0 - 80°C	68 L (18)	550 x 400 x 300 (21.6 x 15.7 x 11.8) (27.5 x 19.8 x 29)	700 x 500 x 740 (4.1 (90))	Stainless steel	1,000 W	1,400 W

*The ME 18G has a 125V 20A, NEMA 5-20, Hospital Grade Plug, which will only plug into a special 115V, 20A amp outlet

